





CENO

SEMI RECESSED | CEILING RECESSED



1.0 SEMI RECESSED

LED COB 6W | 350mA | 17V
excl. driver
aluminium powder coated

IP20 0°-90°/350° A 31° SDCM2 L70I55K 0.14kg

CODE
176561W_
176561B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K	470 >90	3
3000K	500 >90	5

1.0

LED COB 6W | 350mA | 17V
excl. driver
aluminium powder coated

IP20 0°-90°/350° A 39° SDCM2 L70I55K 0.12kg

wire springs 45-47 1.85 4-26

CODE
176161W_
176161G_
176161Q_
176161K_
176161CH_
176161B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K A 31°	470 >90	3
3000K A 31°	500 >90	5
2000-3000K 16V	355 >90	9

ALWAYS USE

revision opening required* | 350mA

CODE	
10W dim*	90223402
10W DALI	90243401


more options and specs on page 736

ALWAYS USE


driver | 350mA

CODE	
10W dim	90223402
10W DALI	90243401

more options and specs on page 736



Rev. 001/2023-08



OPTIONAL

honeycomb louver

CODE
90051131

more options and specs on page 736